




## Dimensions

unit: Inch (mm)



## Summary

This NDAA/TAA-compliant MEGApix IP camera provides 5MP resolution at real-time 30fps and includes a 2.7-13.5mm vari-focal p-iris lens with motorized zoom and auto-focus. The camera is powered by Star-Light Plus color in near-total darkness technology for quality video in any lighting conditions and Cold Start at -40° F/-40° C. The unique Snapit housing is easy to install and is IP68-rated.

## Features

- 5MP sensor at real-time 30fps
- Star-Light Plus color in near-total darkness technology
- Vari-focal p-iris lens with motorized zoom and autofocus for complete remote lens control and focused image any time
- Snapit easy installation camera
- True Wide Dynamic Range (WDR) for clear images in challenging light
- Simultaneous streaming and multiple codec options for smart bandwidth management
- Cold Start -40°F (-40°C), allowing the camera to power up in extremely cold environments
- 100' Smart IR with intelligent camera sync for clear B/W images with no need for external light
- Smart DNR 3D digital noise reduction reduces noise and ghosting for motion in low-light environments.
- Privacy zones cover sensitive areas in the camera's field of view.
- Two-way audio for direct communication between the monitoring station and the camera's location
- Local SD card slot for local recording in case of network loss
- Alarm sensor input and relay output for access control integration
- Web server built-in for easy camera management from any browser
- PoE and DC12V for single cable simplified installation
- NDAA/TAA compliant for federal and government projects
- IP68- and IK10-rated camera housing built to last
- 5 year warranty

## Specifications

<b>IMAGE</b>	
Image sensor	5MP 1/2.8" CMOS
Total pixels	2592(H) X 1944(V)
Minimum scene illumination	0.08 lux (color) / 0 lux (B/W)
Video output	Local video output CVBS 1.0V p-p (75Ω), 4:3 aspect ratio
<b>LENS</b>	
Focal length	2.7 - 13.5mm, F1.4
Lens type	Vari-focal p-iris lens with motorized zoom and auto-focus
HFOV / VFOV	96° - 31° / 70° - 24°
IR distance	100ft range
Optical zoom	x5 optical zoom
<b>I/O</b>	
Audio in/out and compression	1 input/1 output, G.711
Alarm in / out	1 input/1 output
<b>OPERATIONAL</b>	
Intelligent Video Analytics	Intrusion, line crossing, counting line, loitering, enter, exit, tamper, object removed, tailgating, direction, stopped, appear, disappear, object left, logical rules.* NOTE: object removed, tailgating, direction, stopped, appear, disappear, object left, and logical rules are available via IVA+ plugin update. For existing cameras, contact your DW sales representative for a complimentary update.
Shutter speed	1/15 - 1/32000
Slow shutter	1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10
Auto gain control	Auto
Day / night	Auto, day (color), night (B/W)
3D digital noise reduction	Smart DNR 3D-DNR
Wide dynamic range (WDR)	True WDR, 120dB
Privacy zone	16 programmable privacy masks
Mirror and flip	Yes
Alarm notifications	E-mail, FTP server, alarm output activation or SD card recording
Memory slot	Micro SD / SDHC / SDXC (card not Included)
<b>NETWORK</b>	
LAN	RJ45 (10/100Base-T)
Video compression type	H.265, H.264, MJPEG
Resolution	H.265, H.264: 2592x1944, 2304x1296, 21MP/1080p, 720p, VGA, D1, CIF MJPEG: 21MP/1080p, 720p, 800x600, VGA, 768x432, D1, CIF
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps - 10Mbps, Multi-rate for Preview and Recording
Bitrate control	Multi-streaming CBR/VBR at H.264, H.265 (controllable frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4, IPv6
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3 (MIB-2), ONVIF
Security	HTTPS (TLS), IP filtering, 802.1x, digest authentication (ID/PW)
ONVIF conformance	Yes
Web viewer	OS: Windows, Mac OS, Linux Browser: Internet Explorer, Google Chrome, Mozilla Firefox, Safari NOTE: Chrome browser is recommended for IVA configuration
Video management software	DW Spectrum
<b>ENVIRONMENTAL</b>	
Operating temperature	-40°F - 122°F (-40°C - 50°C)
Operating humidity	10-90% RH (non-condensing)
IP rating, IK rating	IP68-rated, IK10 impact-resistant
Other certifications	UL listed, CE, FCC, RoHS, NDAA, TAA
<b>ELECTRICAL</b>	
Power requirement	DC12V, PoE IEEE 802.3af Class 3 (Adapter not Included)
Power consumption	DC12V: max 8.3W, PoE: max 10.5W
<b>MECHANICAL</b>	
Material	Snapit aluminum vandal housing, polycarbonate dome
Dimensions	5.47" x 4.93" (139 x 125.4 mm)
Weight	2.75 lbs (1.25kg)
Warranty	5 years warranty

## Accessories (Optional)



DWC-V4CMW  
Ceiling mount bracket



DWC-V4WMW  
Wall mount bracket



866.446.3595

sales@digital-watchdog.com

www.digital-watchdog.com

Built for Users.™

